

Chain-On-Edge Spindle Conveyors

For Liquid and Powder Coating Applications



1.5" Std. Conveyor Series

Spindle Diameter / Load: 0.625" / 5 lbs.
Typical Spindle Centers: 1.5", 3", 6", 9", 12", +
Minimum Turn Diameter: 6"



2" Std. Conveyor Series

Spindle Diameter / Load: 0.750" / 15 lbs.
Typical Spindle Centers: 2", 4", 6", 8", 10", 12", +
Minimum Turn Diameter: 9"



3" Std. Conveyor Series

Spindle Diameter / Load: 1.000" / 30 lbs.
Typical Spindle Centers: 3", 6", 9", 12", 18", 24", +
Minimum Turn Diameter: 12"



3" H.D. Conveyor Series

Spindle Diameter / Load: 1.000" / 100 lbs.
Typical Spindle Centers: 12", 18", 24", 30", 36", +
Minimum Turn Diameter: 18"



4" H.D. Conveyor Series

Spindle Diameter / Load: 1.250" / 200 lbs.
Typical Spindle Centers: 16", 24", 32", 40", 48", +
Minimum Turn Diameter: 24"



Precision Conveyor Technologies, Inc.

A Division of PCT Industries
3785 Lane Road - Perry, Ohio 44081
Ph: (440) 352-6100 - Fx: (440) 352-6123
sales@precisionconveyor.com
www.precisionconveyor.com